

Package: nnTensor (via r-universe)

October 5, 2026

Type Package

Title Non-Negative Tensor Decomposition

Version 1.4.0

Depends R (>= 3.4.0)

Imports methods, MASS, fields, rTensor, plot3D, tagcloud, ggplot2,
Vicus

Suggests knitr, rmarkdown, testthat, dplyr, tweedie

Description Some functions for performing non-negative matrix factorization, non-negative CANDECOMP/PARAFAC (CP) decomposition, non-negative Tucker decomposition, and generating toy model data. See Andrzej Cichock et al (2009) and the reference section of GitHub README.md
<<https://github.com/rikenbit/nnTensor>>, for details of the methods.

License MIT + file LICENSE

URL <https://github.com/rikenbit/nnTensor>

VignetteBuilder knitr

Repository <https://rikenbit.r-universe.dev>

Date/Publication 2026-05-08 11:44:07 UTC

RemoteUrl <https://github.com/rikenbit/nntensor>

RemoteRef HEAD

RemoteSha 296d46be10e7416ad9408a6aea6fee42248a089e

Contents

nnTensor-package	2
GabrielNMF	4
jNMF	5
kFoldMaskTensor	7
NMF	8
NMTF	11

NTD	13
NTF	15
plot.NMF	17
plotTensor2D	18
plotTensor3D	19
PSDTF	19
recTensor	21
siNMF	22
toyModel	24
ZITNMF	24
Index	27

nnTensor-package	<i>Non-Negative Tensor Decomposition</i>
------------------	--

Description

Some functions for performing non-negative matrix factorization, non-negative CANDECOMP/PARAFAC (CP) decomposition, non-negative Tucker decomposition, and generating toy model data. See Andrzej Cichock et al (2009) and the reference section of GitHub README.md <<https://github.com/rikenbit/nnTensor>>, for details of the methods.

Details

The DESCRIPTION file: This package was not yet installed at build time.

Index: This package was not yet installed at build time.

Author(s)

Koki Tsuyuzaki [aut, cre], Itoshi Nikaido [aut]

Maintainer: Koki Tsuyuzaki <k.t.the-answer@hotmail.co.jp>

References

Andrzej CICHOCK, et. al., (2009). Nonnegative Matrix and Tensor Factorizations. *John Wiley & Sons, Ltd*

Keigo Kimura, (2017). A Study on Efficient Algorithms for Nonnegative Matrix/Tensor Factorization. *Hokkaido University Collection of Scholarly and Academic Papers*

Andrzej CICHOCKI et. al., (2007). Non-negative Tensor Factorization using Alpha and Beta Divergence. *IEEE ICASSP 2007*

Anh Huy PHAN et. al., (2008). Multi-way Nonnegative Tensor Factorization Using Fast Hierarchical Alternating Least Squares Algorithm (HALS). *NOLTA2008*

- Andrzej CICHOCKI et. al., (2008). Fast Local Algorithms for Large Scale Nonnegative Matrix and Tensor Factorizations. *IEICE Transactions on Fundamentals of Electronics, Communications and Computer Sciences*
- Yong-Deok Kim et. al., (2007). Nonnegative Tucker Decomposition. *IEEE Conference on Computer Vision and Pattern Recognition*
- Yong-Deok Kim et. al., (2008). Nonnegative Tucker Decomposition With Alpha-Divergence. *IEEE International Conference on Acoustics, Speech and Signal Processing*
- Anh Huy Phan, (2008). Fast and efficient algorithms for nonnegative Tucker decomposition. *Advances in Neural Networks - ISNN2008*
- Anh Hyu Phan et. al. (2011). Extended HALS algorithm for nonnegative Tucker decomposition and its applications for multiway analysis and classification. *Neurocomputing*
- Jean-Philippe Brunet. et. al., (2004). Metagenes and molecular pattern discovery using matrix factorization. *PNAS*
- Xiaoxu Han. (2007). CANCER MOLECULAR PATTERN DISCOVERY BY SUBSPACE CONSENSUS KERNEL CLASSIFICATION
- Attila Frigyesi. et. al., (2008). Non-Negative Matrix Factorization for the Analysis of Complex Gene Expression Data: Identification of Clinically Relevant Tumor Subtypes. *Cancer Informatics*
- Haesun Park. et. al., (2019). Lecture 3: Nonnegative Matrix Factorization: Algorithms and Applications. *SIAM Gene Golub Summer School, Aussois France, June 18, 2019*
- Chunxuan Shao. et. al., (2017). Robust classification of single-cell transcriptome data by nonnegative matrix factorization. *Bioinformatics*
- Paul Fogel (2013). Permuted NMF: A Simple Algorithm Intended to Minimize the Volume of the Score Matrix
- Philip M. Kim. et. al., (2003). Subsystem Identification Through Dimensionality Reduction of Large-Scale Gene Expression Data. *Genome Research*
- Lucie N. Hutchins. et. al., (2008). Position-dependent motif characterization using non-negative matrix factorization. *Bioinformatics*
- Patrik O. Hoyer (2004). Non-negative Matrix Factorization with Sparseness Constraints. *Journal of Machine Learning* 5
- N. Fujita et al., (2018) Biomarker discovery by integrated joint non-negative matrix factorization and pathway signature analyses, *Scientific Report*
- Art B. Owen et. al., (2009). Bi-Cross-Validation of the SVD and the Nonnegative Matrix Factorization. *The Annals of Applied Statistics*

See Also

[toyModel,NMF,NTF,NTD,recTensor,plotTensor3D](#)

Examples

```
ls("package:nnTensor")
```

GabrielNMF	<i>Gabriel-type Bi-Cross-Validation for Non-negative Matrix Factorization</i>
------------	---

Description

The input data is assumed to be non-negative matrix. GabrielNMF devides the input file into four matrices (A, B, C, and D) and perform cross validation by the prediction of A from the matrices B, C, and D.

Usage

```
GabrielNMF(X, J = 3, nx = 5, ny = 5, ...)
```

Arguments

X	The input matrix which has N-rows and M-columns.
J	The number of low-dimension ($J < \{N, M\}$).
nx	The number of hold-out in row-wise direction ($2 < nx < N$).
ny	The number of hold-out in row-wise direction ($2 < ny < M$).
...	Other parameters for NMF function.

Value

TestRecError : The reconstruction error calculated by Gabriel-style Bi-Cross Validation.

Author(s)

Koki Tsuyuzaki

References

Art B. Owen et. al., (2009). Bi-Cross-Validation of the SVD and the Nonnegative Matrix Factorization. *The Annals of Applied Statistics*

Examples

```
if(interactive()){
  # Test data
  matdata <- toyModel(model = "NMF")

  # Bi-Cross-Validation
  BCV <- rep(0, length=5)
  names(BCV) <- 2:6
  for(j in seq(BCV)){
    print(j+1)
    BCV[j] <- mean(GabrielNMF(matdata, J=j+1, nx=2, ny=2)$TestRecError)
  }
}
```

```

proper.rank <- as.numeric(names(BCV)[which(BCV == min(BCV))])

# NMF
out <- NMF(matdata, J=proper.rank)
}

```

Description

The input data objects are assumed to be non-negative matrices. jNMF decompose the matrices to two low-dimensional factor matrices simultaneously.

Usage

```

jNMF(X, M=NULL, pseudocount=.Machine$double.eps,
     initW=NULL, initV=NULL, initH=NULL, fixW=FALSE, fixV=FALSE,
     fixH=FALSE,
     L1_W=1e-10, L1_V=1e-10, L1_H=1e-10,
     L2_W=1e-10, L2_V=1e-10, L2_H=1e-10,
     J = 3, w=NULL, algorithm = c("Frobenius", "KL", "IS", "PLTF"),
     p=1, thr = 1e-10, num.iter = 100, viz = FALSE,
     figdir = NULL, verbose = FALSE)

```

Arguments

X	A list containing input matrices (X_k , $\langle N \times M_k \rangle$, $k=1..K$).
M	A list containing the mask matrices (X_k , $\langle N \times M_k \rangle$, $k=1..K$). If the input matrix has missing values, specify the element as 0 (otherwise 1).
pseudocount	The pseudo count to avoid zero division, when the element is zero (Default: Machine Epsilon).
initW	The initial values of factor matrix W, which has N-rows and J-columns (Default: NULL).
initV	A list containing the initial values of multiple factor matrices (V_k , $\langle N \times J \rangle$, $k=1..K$, Default: NULL).
initH	A list containing the initial values of multiple factor matrices (H_k , $\langle M_k \times J \rangle$, $k=1..K$, Default: NULL).
fixW	Whether the factor matrix W is updated in each iteration step (Default: FALSE).
fixV	Whether the factor matrices V_k are updated in each iteration step (Default: FALSE).
fixH	Whether the factor matrices H_k are updated in each iteration step (Default: FALSE).
L1_W	Paramter for L1 regularitation (Default: 1e-10). This also works as small positive constant to prevent division by zero, so should be set as 0.

L1_V	Paramter for L1 regularitation (Default: 1e-10). This also works as small positive constant to prevent division by zero, so should be set as 0.
L1_H	Paramter for L1 regularitation (Default: 1e-10). This also works as small positive constant to prevent division by zero, so should be set as 0.
L2_W	Paramter for L2 regularitation (Default: 1e-10).
L2_V	Paramter for L2 regularitation (Default: 1e-10).
L2_H	Paramter for L2 regularitation (Default: 1e-10).
J	Number of low-dimension ($J < N, M_k$).
w	Weight vector (Default: NULL)
algorithm	Divergence between X and $\bar{X}$. "Frobenius", "KL", and "IS" are available (Default: "KL").
p	The parameter of Probabilistic Latent Tensor Factorization (p=0: Frobenius, p=1: KL, p=2: IS)
thr	When error change rate is lower than thr, the iteration is terminated (Default: 1E-10).
num.iter	The number of interation step (Default: 100).
viz	If viz == TRUE, internal reconstructed matrix can be visualized.
figdir	the directory for saving the figure, when viz == TRUE.
verbose	If verbose == TRUE, Error change rate is generated in console windos.

Value

W : A matrix which has N-rows and J-columns ($J < N, M_k$). V : A list which has multiple elements containing N-rows and J-columns ($J < N, M_k$). H : A list which has multiple elements containing M_k -rows and J-columns matrix ($J < N, M_k$). RecError : The reconstruction error between data matrix and reconstructed matrix from W and H. TrainRecError : The reconstruction error calculated by training set (observed values specified by M). TestRecError : The reconstruction error calculated by test set (missing values specified by M). RelChange : The relative change of the error.

Author(s)

Koki Tsuyuzaki

References

- Liviu Badea, (2008) Extracting Gene Expression Profiles Common to Colon and Pancreatic Adenocarcinoma using Simultaneous nonnegative matrix factorization. *Pacific Symposium on Biocomputing* 13:279-290
- Shihua Zhang, et al. (2012) Discovery of multi-dimensional modules by integrative analysis of cancer genomic data. *Nucleic Acids Research* 40(19), 9379-9391
- Zi Yang, et al. (2016) A non-negative matrix factorization method for detecting modules in heterogeneous omics multi-modal data, *Bioinformatics* 32(1), 1-8
- Y. Kenan Yilmaz et al., (2010) Probabilistic Latent Tensor Factorization, *International Conference on Latent Variable Analysis and Signal Separation* 346-353
- N. Fujita et al., (2018) Biomarker discovery by integrated joint non-negative matrix factorization and pathway signature analyses, *Scientific Report*

Examples

```
matdata <- toyModel(model = "siNMF_Hard")
out <- jNMF(matdata, J=2, num.iter=2)
```

kFoldMaskTensor

Mask tensors generator to perform k-fold cross validation

Description

The output multiple mask tensors can be immediately specified as the argument `M` for `NTF()` or `NTD()`.

Usage

```
kFoldMaskTensor(X, k=3, seeds=123, sym=FALSE)
```

Arguments

<code>X</code>	An <code>rTensor</code> object.
<code>k</code>	Number of split for k-fold cross validation (Default: 3).
<code>seeds</code>	Random seed to use for <code>set.seed()</code> (Default: 123).
<code>sym</code>	Data will be dropped symmetrically (available only when matrix is specified, Default: FALSE).

Author(s)

Koki Tsuyuzaki

Examples

```
tensordata <- toyModel(model = "CP")
str(kFoldMaskTensor(tensordata, k=5))
```

Description

The input data is assumed to be non-negative matrix. NMF decompose the matrix to two low-dimensional factor matrices. This function is also used as initialization step of tensor decomposition (see also NTF and NTD).

Usage

```
NMF(X, M=NULL, pseudocount=.Machine$double.eps, initU=NULL, initV=NULL,
    fixU=FALSE, fixV=FALSE,
    L1_U=1e-10, L1_V=1e-10, L2_U=1e-10, L2_V=1e-10, J = 3,
    rank.method=c("all", "ccc", "dispersion", "rss", "evan", "residuals",
        "sparseness.basis", "sparseness.coef", "sparseness2.basis",
        "sparseness2.coef", "norm.info.gain.basis", "norm.info.gain.coef",
        "singular", "volume", "condition"), runtime=30,
    algorithm = c("Frobenius", "KL", "IS", "Pearson", "Hellinger", "Neyman",
        "Alpha", "Beta", "ALS", "PGD", "HALS", "GCD", "Projected", "NHR", "DTPP",
        "Orthogonal", "OrthReg", "t", "TV-GNMF"),
    Alpha = 1, Beta = 2, nu = 2,
    eta = 1e-04, thr1 = 1e-10, thr2 = 1e-10, tol = 1e-04,
    num.iter = 100,
    L_graph_U = NULL, L_graph_V = NULL,
    lambda_graph_U = 0, lambda_graph_V = 0,
    graph.method = c("Vicun", "LEM", "HLLC"),
    graph.K = 10, graph.alpha = 0.9,
    lambda_TV = 0, beta_TV = 0,
    viz = FALSE, figdir = NULL, verbose = FALSE)
```

Arguments

X	The input matrix which has N-rows and M-columns.
M	The mask matrix which has N-rows and M-columns. If the input matrix has missing values, specify the elements as 0 (otherwise 1).
pseudocount	The pseudo count to avoid zero division, when the element is zero (Default: Machine Epsilon).
initU	The initial values of factor matrix U, which has N-rows and J-columns (Default: NULL).
initV	The initial values of factor matrix V, which has M-rows and J-columns (Default: NULL).
fixU	Whether the factor matrix U is updated in each iteration step (Default: FALSE).
fixV	Whether the factor matrix V is updated in each iteration step (Default: FALSE).

L1_U	Paramter for L1 regularitation (Default: 1e-10). This also works as small positive constant to prevent division by zero, so should be set as 0.
L1_V	Paramter for L1 regularitation (Default: 1e-10). This also works as small positive constant to prevent division by zero, so should be set as 0.
L2_U	Paramter for L2 regularitation (Default: 1e-10).
L2_V	Paramter for L2 regularitation (Default: 1e-10).
J	The number of low-dimension ($J < \{N, M\}$). If a numerical vector is specified (e.g. 2:6), the appropriate rank is estimated.
rank.method	The rank estimation method (Default: "all"). Only if the J option is specified as a numerical vector longer than two, this option will be active.
runtime	The number of trials to estimate rank (Default: 10).
algorithm	NMF algorithms. "Frobenius", "KL", "IS", "Pearson", "Hellinger", "Neyman", "Alpha", "Beta", "ALS", "PGD", "HALS", "GCD", "Projected", "NHR", "DTPP", "Orthogonal", "OrthReg", "t", and "TV-GNMF" are available (Default: "Frobenius").
Alpha	The parameter of Alpha-divergence.
Beta	The parameter of Beta-divergence.
nu	The degrees of freedom parameter for t-NMF algorithm (Default: 2). Larger values approach Gaussian NMF. Only used when algorithm = "t".
eta	The stepsize for PGD algorithm (Default: 0.0001).
thr1	When error change rate is lower than thr1, the iteration is terminated (Default: 1E-10).
thr2	If the minus-value is generated, replaced as thr2 (Default: 1E-10). This value is used within the internal function .positive().
tol	The tolerance parameter used in GCD algorithm.
num.iter	The number of interation step (Default: 100).
L_graph_U	A pre-computed graph Laplacian matrix for rows ($N \times N$). If NULL and lambda_graph_U > 0, it is computed automatically using Vicus::graphMatrix (Default: NULL).
L_graph_V	A pre-computed graph Laplacian matrix for columns ($M \times M$). If NULL and lambda_graph_V > 0, it is computed automatically using Vicus::graphMatrix (Default: NULL).
lambda_graph_U	The weight for graph regularization on U (Default: 0). When set to a positive value, adds graph Laplacian regularization to the denominator of the multiplicative update rule for U.
lambda_graph_V	The weight for graph regularization on V (Default: 0). When set to a positive value, adds graph Laplacian regularization to the denominator of the multiplicative update rule for V.
graph.method	The method for computing the graph matrix via Vicus::graphMatrix. "Vicus", "LEM", and "HLL" are available (Default: "Vicus").
graph.K	The number of nearest neighbors for graph construction (Default: 10).
graph.alpha	The alpha parameter for Vicus::graphMatrix (Default: 0.9).

lambda_TV	The weight for Total Variation regularization on V. Only used when algorithm = "TV-GNMF" (Default: 0).
beta_TV	The weight for graph regularization in TV-GNMF algorithm. Only used when algorithm = "TV-GNMF" (Default: 0).
viz	If viz == TRUE, internal reconstructed matrix can be visualized.
figdir	The directory for saving the figure, when viz == TRUE.
verbose	If verbose == TRUE, Error change rate is generated in console window.

Value

U : A matrix which has N-rows and J-columns ($J < \{N, M\}$). V : A matrix which has M-rows and J-columns ($J < \{N, M\}$). J : The number of dimension ($J < \{N, M\}$). RecError : The reconstruction error between data tensor and reconstructed tensor from U and V. TrainRecError : The reconstruction error calculated by training set (observed values specified by M). TestRecError : The reconstruction error calculated by test set (missing values specified by M). RelChange : The relative change of the error. Trial : All the results of the trials to estimate the rank. Runtime : The number of the trials to estimate the rank. RankMethod : The rank estimation method.

Author(s)

Koki Tsuyuzaki

References

- Andrzej CICHOCK, et. al., (2009). Nonnegative Matrix and Tensor Factorizations. *John Wiley & Sons, Ltd*
- Keigo Kimura, (2017). A Study on Efficient Algorithms for Nonnegative Matrix/ Tensor Factorization. *Hokkaido University Collection of Scholarly and Academic Papers*
- K. Yoshii, K. Itoyama, and M. Goto (2016). Student's t Nonnegative Matrix Factorization and Positive Semidefinite Tensor Factorization for Single-Channel Audio Source Separation. *ICASSP*, pp.51-55.
- C. Leng, Z. Chen, G. Cai, I. Cheng, Z. Xiong, J. Tian, and A. Basu (2016). Total Variation Constrained Graph Regularized NMF for Medical Image Registration. *IEEE ICIP*.
- D. Cai, X. He, J. Han, and T. S. Huang (2011). Graph Regularized Nonnegative Matrix Factorization for Data Representation. *IEEE Transactions on PAMI*, 33(8), pp.1548-1560.

Examples

```
if(interactive()){
  # Test data
  matdata <- toyModel(model = "NMF")

  # Simple usage
  out <- NMF(matdata, J=5)

  # Rank estimation mode (single method)
  out2 <- NMF(matdata, J=2:10, rank.method="ccc", runtime=3)
  plot(out2)
```

```

# Rank estimation mode (all method)
out3 <- NMF(matdata, J=2:10, rank.method="all", runtime=10)
plot(out3)

# t-NMF (robust to outliers)
out4 <- NMF(matdata, J=5, algorithm="t", nu=2)

# Graph-regularized NMF
out5 <- NMF(matdata, J=5, algorithm="Frobenius",
  lambda_graph_V=0.1, graph.K=5)

# TV-GNMF (Total Variation + Graph regularization)
out6 <- NMF(matdata, J=5, algorithm="TV-GNMF",
  lambda_TV=0.1, beta_TV=0.1,
  lambda_graph_V=0.1, graph.K=5)
}

```

NMTF

Non-negative Matrix Tri-Factorization Algorithms (NMTF)

Description

The input data is assumed to be non-negative matrix. NMTF decompose the matrix to three low-dimensional factor matrices.

Usage

```

NMTF(X, M=NULL, pseudocount=.Machine$double.eps,
  initU=NULL, initS=NULL, initV=NULL,
  fixU=FALSE, fixS=FALSE, fixV=FALSE,
  L1_U=1e-10, L1_S=1e-10, L1_V=1e-10,
  L2_U=1e-10, L2_S=1e-10, L2_V=1e-10,
  orthU=FALSE, orthV=FALSE,
  rank = c(3, 4),
  algorithm = c("Frobenius", "KL", "IS", "ALS", "PG", "COD", "Beta"),
  Beta = 2, root = FALSE, thr = 1e-10, num.iter = 100,
  viz = FALSE, figdir = NULL, verbose = FALSE)

```

Arguments

X	The input matrix which has N-rows and M-columns.
M	The mask matrix which has N-rows and M-columns. If the input matrix has missing values, specify the elements as 0 (otherwise 1).
pseudocount	The pseudo count to avoid zero division, when the element is zero (Default: Machine Epsilon).
initU	The initial values of factor matrix U, which has N-rows and J1-columns (Default: NULL).

initS	The initial values of factor matrix S, which has J1-rows and J2-columns (Default: NULL).
initV	The initial values of factor matrix V, which has M-rows and J2-columns (Default: NULL).
fixU	Whether the factor matrix U is updated in each iteration step (Default: FALSE).
fixS	Whether the factor matrix S is updated in each iteration step (Default: FALSE).
fixV	Whether the factor matrix V is updated in each iteration step (Default: FALSE).
L1_U	Paramter for L1 regularitation (Default: 1e-10).
L1_S	Paramter for L1 regularitation (Default: 1e-10).
L1_V	Paramter for L1 regularitation (Default: 1e-10).
L2_U	Paramter for L2 regularitation (Default: 1e-10).
L2_S	Paramter for L2 regularitation (Default: 1e-10).
L2_V	Paramter for L2 regularitation (Default: 1e-10).
orthU	Whether the column vectors of matrix U are orthogonalized (Default: FALSE).
orthV	Whether the column vectors of matrix V are orthogonalized (Default: FALSE).
rank	The number of low-dimension (J1 (< N) and J2 (< M)) (Default: c(3,4)).
algorithm	NMTF algorithms. "Frobenius", "KL", "IS", "ALS", "PG", "COD", and "Beta" are available (Default: "Frobenius").
Beta	The parameter of Beta-divergence (Default: 2, which means "Frobenius").
root	Whether square root is calculcd in each iteration (Default: FALSE).
thr	When error change rate is lower than thr, the iteration is terminated (Default: 1E-10).
num.iter	The number of iteration step (Default: 100).
viz	If viz == TRUE, internal reconstructed matrix can be visualized.
figdir	The directory for saving the figure, when viz == TRUE.
verbose	If verbose == TRUE, Error change rate is generated in console window.

Value

U : A matrix which has N-rows and J1-columns ($J1 < N$). S : A matrix which has J1-rows and J2-columns. V : A matrix which has M-rows and J2-columns ($J2 < M$). rank : The number of low-dimension ($J1 < N$ and $J2 < M$). RecError : The reconstruction error between data tensor and reconstructed tensor from U and V. TrainRecError : The reconstruction error calculated by training set (observed values specified by M). TestRecError : The reconstruction error calculated by test set (missing values specified by M). RelChange : The relative change of the error. algorithm: algorithm specified.

Author(s)

Koki Tsuyuzaki

References

- Fast Optimization of Non-Negative Matrix Tri-Factorization: Supporting Information, Andrej Copar, et. al., *PLOS ONE*, 14(6), e0217994, 2019
- Co-clustering by Block Value Decomposition, Bo Long et al., *SIGKDD'05*, 2005
- Orthogonal Nonnegative Matrix Tri-Factorizations for Clustering, Chris Ding et. al., *12th ACM SIGKDD*, 2006

Examples

```
if(interactive()){
  # Test data
  matdata <- toyModel(model = "NMF")

  # Simple usage
  out <- NMTF(matdata, rank=c(4,4))
}
```

NTD

Non-negative Tucker Decomposition Algorithms (NTD)

Description

The input data is assumed to be non-negative tensor. NTD decompose the tensor to the dense core tensor (S) and low-dimensional factor matrices (A).

Usage

```
NTD(X, M=NULL, pseudocount=.Machine$double.eps, initS=NULL, initA=NULL,
    fixS=FALSE, fixA=FALSE, L1_A=1e-10, L2_A=1e-10,
    rank = rep(3, length=length(dim(X))),
    modes = seq_along(dim(X)),
    algorithm = c("Frobenius", "KL", "IS", "Pearson", "Hellinger", "Neyman",
                  "HALS", "Alpha", "Beta", "NMF"), init = c("NMF", "ALS", "Random"),
    nmf.algorithm = c("Frobenius", "KL", "IS", "Pearson", "Hellinger", "Neyman",
                     "Alpha", "Beta", "ALS", "PGD", "HALS", "GCD", "Projected", "NHR", "DTPP",
                     "Orthogonal", "OrthReg"),
    Alpha = 1,
    Beta = 2, thr = 1e-10, num.iter = 100, num.iter2 = 10, viz = FALSE,
    figdir = NULL, verbose = FALSE)
```

Arguments

- | | |
|---|--|
| X | K-order input tensor which has $I_1, I_2, \dots$, and I_K dimensions. |
| M | K-order mask tensor which has $I_1, I_2, \dots$, and I_K dimensions. If the mask tensor has missing values, specify the element as 0 (otherwise 1). |

pseudocount	The pseudo count to avoid zero division, when the element is zero (Default: Machine Epsilon).
initS	The initial values of core tensor which has $I_1, I_2, \dots$, and I_K dimensions (Default: NULL).
initA	A list containing the initial values of K factor matrices ($A_k, <I_k \times J_k>$, $k=1..K$, Default: NULL).
fixS	Whether the core tensor S is updated in each iteration step (Default: FALSE).
fixA	Whether the factor matrices A_k are updated in each iteration step (Default: FALSE).
L1_A	Paramter for L1 regularitation (Default: 1e-10). This also works as small positive constant to prevent division by zero, so should be set as 0.
L2_A	Paramter for L2 regularitation (Default: 1e-10).
rank	The number of low-dimension in each mode (Default: 3 for each mode).
modes	The vector of the modes on which to perform the decomposition (Default: 1:K <all modes>).
algorithm	NTD algorithms. "Frobenius", "KL", "IS", "Pearson", "Hellinger", "Neyman", "HALS", "Alpha", "Beta", "NMF" are available (Default: "Frobenius").
nmf.algorithm	NMF algorithms, when the algorithm is "NMF". "Frobenius", "KL", "IS", "Pearson", "Hellinger", "Neyman", "Alpha", "Beta", "ALS", "PGD", "HALS", "GCD", "Projected", "NHR", "DTPP", "Orthogonal", and "OrthReg" are available (Default: "Frobenius").
init	The initialization algorithms. "NMF", "ALS", and "Random" are available (Default: "NMF").
Alpha	The parameter of Alpha-divergence.
Beta	The parameter of Beta-divergence.
thr	When error change rate is lower than thr1, the iteration is terminated (Default: 1E-10).
num.iter	The number of interation step (Default: 100).
num.iter2	The number of NMF interation step, when the algorithm is "NMF" (Default: 10).
viz	If viz == TRUE, internal reconstructed tensor can be visualized.
figdir	the directory for saving the figure, when viz == TRUE (Default: NULL).
verbose	If verbose == TRUE, Error change rate is generated in console windos.

Value

S : K -order tensor object, which is defined as S4 class of rTensor package. A : A list containing K factor matrices. RecError : The reconstruction error between data tensor and reconstructed tensor from S and A . TrainRecError : The reconstruction error calculated by training set (observed values specified by M). TestRecError : The reconstruction error calculated by test set (missing values specified by M). RelChange : The relative change of the error.

Author(s)

Koki Tsuyuzaki

References

Yong-Deok Kim et. al., (2007). Nonnegative Tucker Decomposition. *IEEE Conference on Computer Vision and Pattern Recognition*

Yong-Deok Kim et. al., (2008). Nonnegative Tucker Decomposition With Alpha-Divergence. *IEEE International Conference on Acoustics, Speech and Signal Processing*

Anh Huy Phan, (2008). Fast and efficient algorithms for nonnegative Tucker decomposition. *Advances in Neural Networks - ISNN2008*

Anh Huy Phan et. al. (2011). Extended HALS algorithm for nonnegative Tucker decomposition and its applications for multiway analysis and classification. *Neurocomputing*

See Also

[plotTensor3D](#)

Examples

```
tensordata <- toyModel(model = "Tucker")
out <- NTF(tensordata, rank=c(2,2,2), algorithm="Frobenius",
  init="Random", num.iter=2)
```

NTF

Non-negative CP Decomposition Algorithms (NTF)

Description

The input data is assumed to be non-negative tensor. NTF decompose the tensor to the diagonal core tensor (S) and low-dimensional factor matrices (A).

Usage

```
NTF(X, M=NULL, pseudocount=.Machine$double.eps, initA=NULL,
  fixA=FALSE, L1_A=1e-10, L2_A=1e-10, rank = 3,
  algorithm = c("Frobenius", "KL", "IS", "Pearson", "Hellinger", "Neyman",
    "HALS", "Alpha-HALS", "Beta-HALS", "Alpha", "Beta"),
  init = c("NMF", "ABS-SVD", "ALS", "Random"), Alpha = 1,
  Beta = 2, thr = 1e-10, num.iter = 100, viz = FALSE,
  figdir = NULL, verbose = FALSE)
```

Arguments

X	K-order input tensor which has $I_1, I_2, \dots$, and I_K dimensions.
M	K-order mask tensor which has $I_1, I_2, \dots$, and I_K dimensions. If the mask tensor has missing values, specify the element as 0 (otherwise 1).
pseudocount	The pseudo count to avoid zero division, when the element is zero (Default: Machine Epsilon).
initA	A list containing the initial values of K factor matrices ($A_k, \langle I_k \times J_k \rangle, k=1..K$, Default: NULL).
fixA	Whether the factor matrices A_k are updated in each iteration step (Default: FALSE).
L1_A	Parameter for L1 regularization (Default: $1e-10$). This also works as small positive constant to prevent division by zero, so should be set as 0.
L2_A	Parameter for L2 regularization (Default: $1e-10$).
rank	The number of low-dimension in each mode (Default: 3).
algorithm	NTF algorithms. "Frobenius", "KL", "IS", "Pearson", "Hellinger", "Neyman", "HALS", "Alpha-HALS", "Beta-HALS", "Alpha", and "Beta" are available (Default: "Frobenius").
init	The initialization algorithms. "NMF", "ABS-SVD", "ALS", and "Random" are available (Default: "NMF").
Alpha	The parameter of Alpha-divergence.
Beta	The parameter of Beta-divergence.
thr	When error change rate is lower than thr1, the iteration is terminated (Default: $1E-10$).
num.iter	The number of iteration step (Default: 100).
viz	If viz == TRUE, internal reconstructed tensor can be visualized.
figdir	the directory for saving the figure, when viz == TRUE (Default: NULL).
verbose	If verbose == TRUE, Error change rate is generated in console window.

Value

S : K-order tensor object, which is defined as S4 class of rTensor package. A : A list containing K factor matrices. RecError : The reconstruction error between data tensor and reconstructed tensor from S and A. TrainRecError : The reconstruction error calculated by training set (observed values specified by M). TestRecError : The reconstruction error calculated by test set (missing values specified by M). RelChange : The relative change of the error.

Author(s)

Koki Tsuyuzaki

References

- Andrzej CICHOCKI et. al., (2007). Non-negative Tensor Factorization using Alpha and Beta Divergence. *IEEE ICASSP 2007*
- Anh Huy PHAN et. al., (2008). Multi-way Nonnegative Tensor Factorization Using Fast Hierarchical Alternating Least Squares Algorithm (HALS). *NOLTA2008*
- Andrzej CICHOCKI et. al., (2008). Fast Local Algorithms for Large Scale Nonnegative Matrix and Tensor Factorizations. *IEICE Transactions on Fundamentals of Electronics, Communications and Computer Sciences*

See Also

[plotTensor3D](#)

Examples

```
tensordata <- toyModel(model = "CP")
out <- NTF(tensordata, rank=3, algorithm="Beta-HALS", num.iter=2)
```

plot.NMF

Plot function of the result of NMF function

Description

Only if J is specified as a vector longer than 1, this function will be active.

Author(s)

Koki Tsuyuzaki

References

- Jean-Philippe Brunet. et. al., (2004). Metagenes and molecular pattern discovery using matrix factorization. *PNAS*
- Xiaoxu Han. (2007). CANCER MOLECULAR PATTERN DISCOVERY BY SUBSPACE CONSENSUS KERNEL CLASSIFICATION
- Attila Frigyesi. et. al., (2008). Non-Negative Matrix Factorization for the Analysis of Complex Gene Expression Data: Identification of Clinically Relevant Tumor Subtypes. *Cancer Informatics*
- Haesun Park. et. al., (2019). Lecture 3: Nonnegative Matrix Factorization: Algorithms and Applications. *SIAM Gene Golub Summer School, Aussois France, June 18, 2019*
- Chunxuan Shao. et. al., (2017). Robust classification of single-cell transcriptome data by nonnegative matrix factorization. *Bioinformatics*
- Paul Fogel (2013). Permuted NMF: A Simple Algorithm Intended to Minimize the Volume of the Score Matrix
- Philip M. Kim. et. al., (2003). Subsystem Identification Through Dimensionality Reduction of Large-Scale Gene Expression Data. *Genome Research*

Lucie N. Hutchins. et. al., (2008). Position-dependent motif characterization using non-negative matrix factorization. *Bioinformatics*

Patrik O. Hoyer (2004). Non-negative Matrix Factorization with Sparseness Constraints. *Journal of Machine Learning* 5

Examples

```
methods(class = "NMF")
```

plotTensor2D	<i>Plot function for visualization of matrix data structure</i>
--------------	---

Description

Combined with recTensor function and the result of NTF or NTD, the reconstructed tensor structure can be visullized.

Usage

```
plotTensor2D(X = NULL, method=c("sd", "mad"),
             sign=c("positive", "negative", "both"), thr=2)
```

Arguments

X	Matrix object.
method	Cutoff method to focus on large/small value in the tensor data (Default: "sd").
sign	Direction to cutoff the large/small value in the tensor data (Default: "positive").
thr	Threshold of cutoff method (Default: 2).

Author(s)

Koki Tsuyuzaki

Examples

```
tensordata <- toyModel(model = "CP")

out <- NTF(tensordata, rank=3, num.iter=2)

tmp <- tempdir()

png(filename=paste0(tmp, "/NTF.png"))
plotTensor2D(out$A[[1]])
dev.off()
```

plotTensor3D	<i>Plot function for visualization of tensor data structure</i>
--------------	---

Description

Combined with recTensor function and the result of NTF or NTD, the reconstructed tensor structure can be visullized.

Usage

```
plotTensor3D(X = NULL, method=c("sd", "mad"),
  sign=c("positive", "negative", "both"), thr=2)
```

Arguments

X	Tensor object, which is defined as S4 class of rTensor package.
method	Cutoff method to focus on large/small value in the tensor data (Default: "sd").
sign	Direction to cutoff the large/small value in the tensor data (Default: "positive").
thr	Threshold of cutoff method (Default: 2).

Author(s)

Koki Tsuyuzaki

Examples

```
tensordata <- toyModel(model = "CP")

out <- NTF(tensordata, rank=3, algorithm="Beta-HALS", num.iter=2)

tmp <- tempdir()

png(filename=paste0(tmp, "/NTF.png"))
plotTensor3D(recTensor(out$S, out$A))
dev.off()
```

PSDTF	<i>Positive Semidefinite Tensor Factorization with LogDet Divergence (PSDTF)</i>
-------	--

Description

The input data is assumed to be a three-dimensional array ($M \times M \times N$), where each frontal slice is a positive semidefinite (PSD) matrix. PSDTF approximates each PSD matrix as a weighted sum of K PSD basis matrices using the LogDet divergence.

Usage

```
PSDTF(X, rank=3, initH=NULL, initV=NULL,
      thr=1e-10, num.iter=100, verbose=FALSE)
```

Arguments

<code>X</code>	A three-dimensional array of size $M \times M \times N$, where each frontal slice $X[:,n]$ is a positive semidefinite matrix.
<code>rank</code>	The number of PSD basis matrices (Default: 3).
<code>initH</code>	The initial values of activation matrix H ($K \times N$ non-negative matrix) (Default: NULL).
<code>initV</code>	The initial values of PSD basis matrices, a list of K matrices each of size $M \times M$ (Default: NULL).
<code>thr</code>	The threshold for convergence based on relative change of LogDet divergence (Default: $1e-10$).
<code>num.iter</code>	The number of maximum iterations (Default: 100).
<code>verbose</code>	If verbose is TRUE, the iteration number and error are printed (Default: FALSE).

Value

`H` : The activation coefficient matrix (K -rows and N -columns)
`V` : A list of K PSD basis matrices, each of size $M \times M$
`RecError` : The LogDet divergence values at each iteration
`RelChange` : The relative change of error at each iteration

Author(s)

Koki Tsuyuzaki

References

K. Yoshii, R. Tomioka, D. Mochihashi, and M. Goto, "Beyond NMF: Time-domain audio source separation without phase reconstruction", ISMIR, pp.369-374, 2013.

Examples

```
if(interactive()){
  # Generate toy PSD tensor
  M <- 4
  N <- 10
  K <- 2
  V_true <- list()
  for(k in 1:K){
    A <- matrix(runif(M*M), M, M)
    V_true[[k]] <- A %*% t(A)
  }
  H_true <- matrix(runif(K*N), K, N)
```

```

X <- array(0, dim=c(M, M, N))
for(n in 1:N){
  for(k in 1:K){
    X[, ,n] <- X[, ,n] + H_true[k,n] * V_true[[k]]
  }
}

# Run PSDTF
out <- PSDTF(X, rank=K, num.iter=20, verbose=TRUE)
}

```

recTensor

*Tensor Reconstruction from core tensor (S) and factor matrices (A)***Description**

Combined with plotTensor3D function and the result of NTF or NTD, the reconstructed tensor structure can be visualized.

Usage

```
recTensor(S = NULL, A = NULL, idx = seq_along(dim(S)), reverse = FALSE)
```

Arguments

S	K-order tensor object, which is defined as S4 class of rTensor package.
A	A list containing K factor matrices.
idx	The direction of mode-n multiplication (Default: 1:K). For example idx=1 is defined. S x_1 A is calculated (x_1 : mode-1 multiplication).
reverse	If reverse = TRUE, t(A[[n]]) is multiplied to S (Default: FALSE).

Value

Tensor object, which is defined as S4 class of rTensor package.

Author(s)

Koki Tsuyuzaki

See Also

[Tensor-class](#), [NTF](#), [NTD](#)

Examples

```

tensordata <- toyModel(model = "CP")
out <- NTF(tensordata, rank=3, algorithm="Beta-HALS", num.iter=2)
rec <- recTensor(out$S, out$A)

```

Description

The input data objects are assumed to be non-negative matrices. siNMF decompose the matrices to two low-dimensional factor matrices simultaneously.

Usage

```
siNMF(X, M=NULL, pseudocount=.Machine$double.eps, initW=NULL, initH=NULL,
      fixW=FALSE, fixH=FALSE,
      L1_W=1e-10, L1_H=1e-10, L2_W=1e-10, L2_H=1e-10, J = 3,
      w=NULL, algorithm = c("Frobenius", "KL", "IS", "PLTF"), p=1,
      thr = 1e-10, num.iter = 100,
      viz = FALSE, figdir = NULL, verbose = FALSE)
```

Arguments

X	A list containing the input matrices (X_k , $\langle N \times M_k \rangle$, $k=1..K$).
M	A list containing the mask matrices (X_k , $\langle N \times M_k \rangle$, $k=1..K$). If the input matrix has missing values, specify the element as 0 (otherwise 1).
pseudocount	The pseudo count to avoid zero division, when the element is zero (Default: Machine Epsilon).
initW	The initial values of factor matrix W, which has N-rows and J-columns (Default: NULL).
initH	A list containing the initial values of multiple factor matrices (H_k , $\langle M_k \times J \rangle$, $k=1..K$, Default: NULL).
fixW	Whether the factor matrix W is updated in each iteration step (Default: FALSE).
fixH	Whether the factor matrices H_k are updated in each iteration step (Default: FALSE).
L1_W	Parameter for L1 regularization (Default: 1e-10). This also works as small positive constant to prevent division by zero, so should be set as 0.
L1_H	Parameter for L1 regularization (Default: 1e-10). This also works as small positive constant to prevent division by zero, so should be set as 0.
L2_W	Parameter for L2 regularization (Default: 1e-10).
L2_H	Parameter for L2 regularization (Default: 1e-10).
J	Number of low-dimension ($J < N$, M_k).
w	Weight vector (Default: NULL)
algorithm	Divergence between X and X_{bar} . "Frobenius", "KL", and "IS" are available (Default: "KL").
p	The parameter of Probabilistic Latent Tensor Factorization (p=0: Frobenius, p=1: KL, p=2: IS)

thr	When error change rate is lower than thr, the iteration is terminated (Default: 1E-10).
num.iter	The number of iteration step (Default: 100).
viz	If viz == TRUE, internal reconstructed matrix can be visualized.
figdir	the directory for saving the figure, when viz == TRUE.
verbose	If verbose == TRUE, Error change rate is generated in console windos.

Value

W : A matrix which has N-rows and J-columns ($J < N$, Mk). H : A list which has multiple elements containing Mk-rows and J-columns matrix ($J < N$, Mk). RecError : The reconstruction error between data matrix and reconstructed matrix from W and H. TrainRecError : The reconstruction error calculated by training set (observed values specified by M). TestRecError : The reconstruction error calculated by test set (missing values specified by M). RelChange : The relative change of the error.

Author(s)

Koki Tsuyuzaki

References

- Liviu Badea, (2008) Extracting Gene Expression Profiles Common to Colon and Pancreatic Adenocarcinoma using Simultaneous nonnegative matrix factorization. *Pacific Symposium on Biocomputing* 13:279-290
- Shihua Zhang, et al. (2012) Discovery of multi-dimensional modules by integrative analysis of cancer genomic data. *Nucleic Acids Research* 40(19), 9379-9391
- Zi Yang, et al. (2016) A non-negative matrix factorization method for detecting modules in heterogeneous omics multi-modal data, *Bioinformatics* 32(1), 1-8
- Y. Kenan Yilmaz et al., (2010) Probabilistic Latent Tensor Factorization, *International Conference on Latent Variable Analysis and Signal Separation* 346-353
- N. Fujita et al., (2018) Biomarker discovery by integrated joint non-negative matrix factorization and pathway signature analyses, *Scientific Report*

Examples

```
matdata <- toyModel(model = "siNMF_Easy")
out <- siNMF(matdata, J=2, num.iter=2)
```

toyModel	<i>Toy model data for using NMF, NTF, and NTD</i>
----------	---

Description

The data is used for confirming the algorithm are properly working.

Usage

```
toyModel(model = "CP", seeds=123)
```

Arguments

model	Single character string is specified. "NMF", "CP", and "Tucker" are available (Default: "CP").
seeds	Random number for setting set.seeds in the function (Default: 123).

Value

If model is specified as "NMF", a matrix is generated. Otherwise, a tensor is generated.

Author(s)

Koki Tsuyuzaki

See Also

[NMF](#), [NTF](#), [NTD](#)

Examples

```
matdata <- toyModel(model = "NMF", seeds=123)
tensordata1 <- toyModel(model = "CP", seeds=123)
tensordata2 <- toyModel(model = "Tucker", seeds=123)
```

ZITNMF	<i>Zero-Inflated Tweedie Non-negative Matrix Factorization (ZITNMF)</i>
--------	---

Description

The input data is assumed to be a non-negative matrix with excess zeros. ZITNMF decomposes the matrix into two low-dimensional factor matrices while accounting for zero inflation using a Tweedie distribution model.

Usage

```
ZITNMF(X, Z=NULL, pseudocount=1e-10,
       initF=NULL, initA=NULL, initW=0.5, fixF=FALSE, fixA=FALSE,
       initializer=c("NMF", "ALS", "Random"),
       J=3, Beta=2, phi=1, thr=1e-10, num.iter=100, verbose=FALSE)
```

Arguments

X	The input non-negative matrix which has N-rows and M-columns.
Z	The zero-inflation indicator matrix which has N-rows and M-columns (Default: NULL). If NULL, it is estimated from the data.
pseudocount	The pseudo count to avoid zero division (Default: 1e-10).
initF	The initial values of factor matrix F, which has N-rows and J-columns (Default: NULL).
initA	The initial values of factor matrix A, which has M-rows and J-columns (Default: NULL).
initW	The initial value of zero-inflation probability w, a scalar between 0 and 1 (Default: 0.5).
fixF	Whether the factor matrix F is updated in each iteration step (Default: FALSE).
fixA	Whether the factor matrix A is updated in each iteration step (Default: FALSE).
initializer	The initialization method for factor matrices (Default: "NMF"). "NMF" uses Beta-divergence NMF, "ALS" uses SVD-based initialization, and "Random" uses random uniform values.
J	The number of low-dimension (Default: 3).
Beta	The Beta parameter for Beta-divergence. Beta=2 corresponds to Frobenius norm, Beta=1 to KL divergence, Beta=0 to IS divergence (Default: 2). Note that Beta < 1 requires the tweedie package.
phi	The dispersion parameter for the Tweedie distribution (Default: 1).
thr	The threshold for convergence based on relative change of Beta-divergence (Default: 1e-10). If NULL, no convergence check is performed and all num.iter iterations are run.
num.iter	The number of maximum iterations (Default: 100).
verbose	If verbose is TRUE, the iteration number and Beta-divergence value are printed (Default: FALSE).

Value

F : The factor matrix (N-rows and J-columns)
A : The factor matrix (M-rows and J-columns)
Z : The estimated zero-inflation indicator matrix (N-rows and M-columns)
w : The estimated zero-inflation probability (scalar)
RecError : The Beta-divergence values at each iteration
RelChange : The relative change of Beta-divergence at each iteration

Author(s)

Koki Tsuyuzaki

References

Zero-inflated models for count data and their extensions.

Examples

```
if(interactive()){  
  # Test data  
  X <- toyModel("NMF")  
  
  # Frobenius  
  out <- ZITNMF(X, J=3, Beta=2, num.iter=10, initializer="Random")  
  
  # KL  
  out <- ZITNMF(X, J=3, Beta=1, num.iter=10, initializer="Random")  
}
```

Index

* **methods**

- GabrielNMF, [4](#)
- jNMF, [5](#)
- kFoldMaskTensor, [7](#)
- NMF, [8](#)
- NMTF, [11](#)
- NTD, [13](#)
- NTF, [15](#)
- plot.NMF, [17](#)
- plotTensor2D, [18](#)
- plotTensor3D, [19](#)
- PSDTF, [19](#)
- recTensor, [21](#)
- siNMF, [22](#)
- toyModel, [24](#)
- ZITNMF, [24](#)

* **package**

- nnTensor-package, [2](#)

GabrielNMF, [4](#)

jNMF, [5](#)

kFoldMaskTensor, [7](#)

NMF, [3](#), [8](#), [24](#)

NMTF, [11](#)

nnTensor (nnTensor-package), [2](#)

nnTensor-package, [2](#)

NTD, [3](#), [13](#), [21](#), [24](#)

NTF, [3](#), [15](#), [21](#), [24](#)

plot (plot.NMF), [17](#)

plot.NMF, [17](#)

plotTensor2D, [18](#)

plotTensor3D, [3](#), [15](#), [17](#), [19](#)

PSDTF, [19](#)

recTensor, [3](#), [21](#)

siNMF, [22](#)

toyModel, [3](#), [24](#)

ZITNMF, [24](#)